



P R E M I E R
ENVIRONMENTAL

HOMEOWNER'S MANUAL

ON-SITE WASTEWATER COLLECTION & TREATMENT SYSTEMS

How to Take Care of Your Wastewater System

Information Provided by:

Orenco[®]
SYSTEMS

Protecting the World's Water ... Every. Single. Day.

www.orenco.com

INSIDE THE HOUSE: *Do & Don't*

There are a number of do's and don'ts that will help to ensure a long life and minimal maintenance for your system. As a general rule, nothing should be disposed into any wastewater system that hasn't first been ingested, other than toilet tissue, mild detergents, and wash water. Here are some additional guidelines.



Don't flush dangerous and damaging substances into your wastewater treatment system. (Please refer to the "Substitutes for Household Hazardous Waste," on the next panel.) Specifically, do not flush ...

- Pharmaceuticals
- Excessive amounts of bath or body oils
- Water softener backwash
- Flammable or toxic products
- Household cleaners, especially floor wax and rug cleaners
- Chlorine bleach, chlorides, and pool or spa products
- Pesticides, herbicides, agricultural chemicals, or fertilizers



Don't use special additives that are touted to enhance the performance of your tank or system. Additives can cause major damage to other areas in the collection system. The natural microorganisms that grow in your system generate their own enzymes that are sufficient for breaking down and digesting nutrients in the wastewater.



Don't ignore leaky plumbing fixtures; repair them. A leaky toilet can waste up to 2,000 gallons of water in a single day. That's 10-20 times more water than a household's typical daily usage. Leaky plumbing fixtures increase your water bill, waste natural resources, and overload your system.



Don't leave interior faucets on to protect water lines during cold spells. A running faucet can easily increase your wastewater flow by 1,000 to 3,000 gallons per day and hydraulically overload your system. Instead, properly insulate or heat your faucets and plumbing.



Do keep lint out of your wastewater treatment system by cleaning the lint filters on your washing machine and dryer before every load. Installing a supplemental lint filter on your washing machine would be a good precautionary measure. (This normally takes just a few minutes. Lint and other such materials can make a big difference in the frequency and cost of pumping out your primary treatment tank.)



Do use your trash can to dispose of substances that cause maintenance problems and/or increase the need for septage pumping.

Dispose of the following with your trash:

- Egg shells, cantaloupe seeds, gum, coffee grounds
- Tea bags, chewing tobacco, cigarette butts
- Paper towels, newspapers, sanitary napkins, diapers, or kitty litter
- Rags, large amounts of hair



Do collect grease in a container and dispose with your trash. And avoid using garbage disposals excessively. Compost scraps or dispose with your trash, also. Food by-products accelerate the need for septage pumping and increase maintenance.



Don't use excessive amounts of water. Using 50 gallons per person per day is typical. If your household does not practice any of the "water-conserving tips" below, you may be using too much water.

DO conserve water:

- Take shorter showers or take baths with a partially filled tub.
- Be cautious about excessive use of large soaking tubs.
- Don't let water run while brushing teeth, washing hands, etc.
- Wash dishes and clothes when you have a full load.
- When possible, avoid doing several loads in one day.
- Use water-saving devices on faucets and shower heads.
- When replacing old toilets, buy low-flush models.



Do use substitutes for household hazardous waste. Replace the following hazardous products with products that are less environmentally harmful. The hazardous cleaners are listed below, followed by the suggested substitute.

Ammonia-based cleaners:

Sprinkle baking soda on a damp sponge. For windows, use a solution of 2 tbs white vinegar to 1 qt water. Pour the mixture into a spray bottle.

Disinfectants:

Use borax: 1/2 cup in a gallon of water, deodorizes also.

Drain decloggers:

Use a plunger or metal snake, or remove and clean trap.

Scouring cleaners & powders:

Sprinkle baking soda on a damp sponge or add 4 tbs baking soda to 1 qt warm water. Or use Bon Ami; it's cheaper and won't scratch.

Carpet/upholstery cleaners:

Sprinkle dry cornstarch or baking soda on, then vacuum. For tougher stains, blot with white vinegar in soapy water.

Toilet cleaners:

Sprinkle on baking soda or Bon Ami; then scrub with a toilet brush.

Furniture/floor polishes:

To clean, use oil soap and warm water.

Dry with soft cloth. Polish with 1 part lemon juice and 2 parts oil (any kind), or use natural products with lemon oil or beeswax in mineral oil.

Metal cleaners:

- Brass and copper: scrub with a used half of lemon dipped in salt.
- Stainless steel: use scouring pad and soapy water
- Silver: rub gently with toothpaste and soft wet cloth.

Oven cleaners:


Quickly sprinkle salt on drips; then scrub.

Use baking soda and scouring pads on older spills.



Laundry Detergents: Choose a liquid detergent (not a powder) that doesn't have chlorine or phosphates.

AT THE CONTROL PANEL



Do locate your electrical control panel where it will be protected from potential vandalism and have unobstructed access.

Do familiarize yourself with the location of your wastewater system and electrical control panel. Refer to the panel's model and UL number (inside the door panel) when reporting a malfunction in the system.

Do take immediate action to correct the problem in the event of an alarm condition. Call your system operator or maintenance company immediately whenever an alarm comes on. (It sounds like a smoke alarm.)



Do remember that the audible alarm can be silenced by pushing the lighted button located directly above the "Push to Silence" label on the front of the electrical control panel. With normal use, the tank has a reserve storage capacity good for 24-48 hours.

Don't turn off the main circuit breaker to the wastewater pumps when going on vacation. If there is any infiltration or inflow into the system, the pumps will need to handle it.

IMPORTANT! CAUTION!

Only a qualified electrician or authorized installer/operator should work on your control panel. Before anyone does any work on either the wiring to the level control floats and pumps in the vault or on the control panel itself, it is imperative to first switch the isolation fuse/ breaker and the circuit breakers in the panel to the "Off" positions, then switch "Off" the power to the system at the main breaker!



PREMIER
ENVIRONMENTAL

OUTSIDE THE HOUSE: *Do & Don't*



Don't enter your tank. Entering an underground tank without the necessary confined space entry training and procedures can result in death from asphyxiation or drowning. Keep children away from tank openings if lids are off or lid bolts are removed.

Do keep the tank access lid fastened to the riser at all times with stainless steel lid bolts. If the lid or riser becomes damaged in any way, **BLOCK ACCESS TO THE TANK OPENING, IMMEDIATELY.**

Then call your service provider to repair it. If you or your service provider needs replacement bolts, call Orenco at 800-348-9843.



Don't dump RV waste into your wastewater system. It will increase the frequency of required septage pumping. When dumped directly into the pumping vault, RV waste clogs or fouls equipment, causing undue maintenance and repair costs. (Also, some RV waste may contain chemicals that are toxic or that may retard the biological digestion occurring within the tank)

Don't ever connect rain gutters or storm drains to the sewer or allow surface water to drain into it. And don't discharge hot-tub water into your system. The additional water will increase costs, reduce the capacity of the collection and treatment systems, and flood the drainfield. It can also wash excess solids through the tank.



Don't dig without knowing the location of your wastewater system. As much as possible, plan landscaping and permanent outdoor structures before installation. But easily removable items, such as bird baths and picnic tables, are OK to place on top of your system.



Don't drive over your tank or any buried components in your system, unless it's been equipped with a special traffic lid. If the system is subject to possible traffic, put up a barricade or a row of shrubs.



Do make arrangements with a reliable service person to provide regular monitoring and maintenance. Place the service person's phone number on or in your control panel!

Do keep a file copy of your service provider's sludge and scum monitoring report and pumpout schedule. This information will be beneficial for real estate transactions or regulatory visits.

Do keep an "as built" system diagram in a safe place for reference.